



RACEMASTER

The *First* Drag Tire

Master of the Track

FSB BOYS



DRAG RACE SLICKS



SIZE	P. CODE	T.W.	S.W.	CIR.	RIM
8.0/22.0-13**	MHR-03	8.0	10.0	70.0	8.0
9.0/22.0-13**	MHR-05	9.0	10.5	70.0	8.0
8.0/23.0-13**	MHR-04	8.0	10.0	72.5	8.0
8.5/24.5-13**	MHR-09	8.5	10.5	76.8	8.0
9.5/24.5-13**	MHR-19	9.5	11.1	77.0	8.0
8.7/25.0-13XT**	MHR-15	8.7	10.9	78.5	8.0
8.00/8.50-14*** VINTAGE NEW!	MVD-006	7.0	9.8	88.0	6.5
8.5/26.0-13XT**	MHR-14	8.5	10.5	82.0	8.0
7.5/23-15**	MHR-21	7.3	8.2	73.0	6.0
8.5/23.0-15**	MHR-23	8.3	9.4	73.0	8.0
8.5/24.5-15**	MHR-25	8.5	10.0	77.0	8.0
6.0/26.0-15**	MHR-60	6.0	8.5	81.7	6.0
8.5/26.0-15**	MHR-62	8.3	10.5	82.0	8.0
10.0/26.0-15**	MHR-64	10.0	11.1	82.0	8.0
12.0/26.0-15***	MHR-66	12.0	13.5	82.0	10.0
9.0/27.0-15**	MHR-33	9.0	11.1	85.0	8.0
10.0/27.0-15***	MHR-68	10.3	12.1	86.0	9.0
9.0/28.0-15***	MHR-70	9.0	11.0	88.0	8.0
9.0/28.0-15XT***	MHR-37	9.3	11.8	88.5	8.0
10.5/28.0-15***	MHR-50	10.5	12.2	88.3	10.0
10.5/28.5-15***	MHR-52	10.5	13.2	91.1	10.0
12.0/29.0-15***	MHR-73	12.2	14.2	91.1	10.0
9.0/30.0-15***	MHR-76	9.0	11.9	94.0	8.0
10.5/30.0-15***	MHR-78	10.5	13.3	94.2	10.0
10.5/30.5-15W***	MHR-94	11.5	14.5	96.2	10.0
11.5/30.5-15***	MHR-80	11.5	14.5	96.2	10.0
12.0/30.5-15XT***	MHR-82	12.5	15.0	95.8	10.0
13.0/30.0-15***	MHR-84	13.0	16.0	94.2	14.0
13.0/31.0-15***	MHR-86	13.0	17.0	98.8	14.0
14.0/32.0-15***	MHR-88	14.5	18.0	101.0	14.0
10.5/33.0-15W***	MHR-89	11.3	14.7	102.7	10.0
12.0/33.-15* NEW!	MHR-69	12.3	15.9	102.0	12.0
14.5/33.0-15***	MHR-90	14.5	18.5	103.8	14.0
17.0/33-15*	MHR-98	16.7	21.0	102.0	16.0
5.0/26.0-16** H/D M.C.	MHR-58	4.9	6.5	81.7	4.0
12.0/26.0-16***	MHR-91	12.0	13.7	82.3	11.0
12.00/16* NOSTALGIA!	MVD-004	11.6	13.6	100.0	10.0
13.00/16* NOSTALGIA!	MVD-005	12.2	15.4	101.0	12.0
17.0/33.0-16*	MHR-97	17.4	20.8	105.0	16.0
17.0/34.6-16*	MHR-95	17.0	21.0	109.8	16.0
17.0/36.0-16*	MHR-96	17.0	21.4	114.0	16.0

Compounds: *#8, **HB11, ***#704. XT for Extreme Traction Requirements

CHEATER SLICK DRAG RACE TIRES

SIZE	COM. RACE SIZE	P. CODE	T.W.	S.W.	DIA.	CIR.	RIM
26/10.5-15LT	8.5/26.0-15	MHD 01	8.5	10.5	26.0	81.8	8.0
26/11.5-15LT	10.0/26.0-15	MHD 02	10.0	12.3	26.0	82.0	10.0
28/12.5-15LT	10.0/28.0-15	MHD 04	10.0	12.5	28.0	88.0	10.0
28/14.0-15LT	10.5/28.0-15	MHD 07	10.5	13.3	28.0	88.0	10.0
28/14.5-15LT	11.5/28.0-15	MHD 09	11.5	14.1	28.2	88.4	11.0
30/14.0-15LT*	11.0/30.0-15	MHD-10	11.0	14.0	30.0	94.0	10.0
30/14.5-15LT	12.0/30.0-15	MHD 12	12.0	14.7	30.0	94.2	11.0
26/11.5-16LT	10.0/26.0-16	MHD 03	10.0	11.8	26.0	92.0	10.0
28/12.5-16LT*	10.5/28.0-16	MHD 05	10.5	12.4	28.0	88.0	10.0
28/13.5-16LT*	11.5/28.0-16	MHD 08	11.5	13.4	28.0	88.0	11.0
30/14.0-16LT	11.0/30.0-16	MHD 11	11.0	14.0	30.0	94.0	10.0
30/14.5-16LT	12.0/30.0-16	MHD 13	12.0	14.5	30.2	94.2	11.0



DOT Certified - Wrinkle Wall Tube Type. Designed For Dry Pavement Racing Only. Compound #HB-11

*Non-Stocking Item - Special Order Only



For the most current info on M&H tire sizes, availability & specs visit - www.mhracemaster.com

RADIAL DRAG RACING TIRES

SIZE	COM. RACE SIZE	P. CODE	T.W.	S.W.	DIA.	CIR.	RIM
REAR							
275/60R15	9.0/28.0R15	ROD-03	8.8	10.6	28.0	88.0	8.0
325/50R15	10.5/28.0R15	ROD-04	10.3	12.3	28.0	88.0	11.0
390/45R15	12.5/29.5R15	ROD-07	12.5	14.8	29.5	92.7	12.0
275/55R16	9.0/28.0R16	ROD-08	8.8	10.4	28.0	88.0	9.0
275/50R17	9.0/28.0R17	ROD-06	8.8	10.1	28.0	88.0	9.0
325/45R17	10.5/28.0R17	ROD-05	10.3	12.1	28.0	88.0	11.0
390/40R17	12.0/29.5R17	ROD-09	12.5	14.3	29.5	92.7	12.0
275/45R18 NEW!	9.0/28.0R18	ROD-13	8.8	9.8	28.0	88.0	9.0
325/40R18 NEW!	10.5/28.0R18	ROD-14	10.3	11.3	28.0	88.0	11.0
345/35R18 NEW!	12.0/28.0R18	ROD-15	12.1	13.3	28.0	88.0	12.0
FRONT							
185/75R15		ROD-02R	5.0	6.7	26.0	81.7	5.0
185/55R17		ROD-11R	5.0	6.6	26.0	81.7	5.0
185/50R18		ROD-12R	5.0	6.5	26.0	81.7	5.0

DOT Certified - Tubeless



MUSCLE CAR DRAG RACE TIRES

SIZE		COM. RACE SIZE	P. CODE	T.W.	S.W.	DIA.	CIR.	RIM
P205/60-13	G	7.5/23.0-13	MSS-012	7.2	8.8	22.8	71.6	6.0
P235/60-14	G	7.5/25.0-14	MSS-002	7.5	9.8	25.0	78.4	6.5
P215/65-15	D	6.0/26.0-15	MSS-016	6.0	8.4	26.0	81.6	6.0
P235/60-15	G	7.5/25.5-15	MSS-008	7.5	9.8	25.4	80.0	6.5
G60/15	D	8.0/26.0-15	MSS-003	7.8	10.3	26.2	82.3	7.0
J60/15	D	8.0/27.0-15	MSS-004	8.0	10.7	27.2	85.4	7.0
P275/50-15	C	10.0/26.0-15	MSS-005	10.0	11.6	26.2	82.3	9.0
P275/60-15	B	10.0/28.0-15	MSS-001	10.0	11.7	28.2	88.5	9.0
N50/15	B	11.0/28.0-15	MSS-006	11.0	12.8	28.2	88.5	10.0
29x17-15LT	C	13.0/29.0-15	MSS-011	13.2	17.0	29.0	91.0	13.0
30x18-15LT	F	14.5/30.0-15	MSS-010	14.5	18.0	30.0	94.0	14.0
33x18-15LT	B	14.5/33.0-15	MSS-009	14.5	19.0	33.0	104.0	14.0
P305/40-16	C	10.0/26.0-16	MSS-007	10.0	11.9	26.0	81.6	10.0
33/15.50-16LT	B	12.0/33.0-16	MSS-013	12.2	16.0	33.0	104.0	12.0

DOT Certified-Wrinkle Wall - Tubeless or Tube Type, Compound #703



MUSCLE CAR B



MUSCLE CAR F



MUSCLE CAR C



MUSCLE CAR D



MUSCLE CAR G



For the most current info on M&H tire sizes, availability & specs visit - www.mhracemaster.com



DRAG RACING FRONT RUNNERS

SIZE		P. CODE	T.W.	S.W.	CIR.	RIM
3.5/22-15 (P145/65-15)	RIB	MSS-021	4.0	5.5	69.5	4.0
3.6/24-15 (P165/70-15)	RIB	MSS-022	4.0	6.2	74.9	4.0
4.5/24-15 (P175/70-15)	NEW! RIB	MSS-023	4.7	6.6	75.2	4.0
4.5/26-15 (P175/75-15)	RIB	MSS-018	4.5	6.5	81.2	4.0
4.5/27-15 (P185/85-15)	RIB	MSS-014	4.5	7.0	85.6	4.0
4.5/27-16 (P185/80-16)	RIB	MSS-015	4.5	6.8	85.6	4.0
4.5/26-17 (P165/70-17)	RIB	MSS-017	4.5	6.0	81.7	4.0

Rib Tread--D.O.T. Certified

RACING TUBES

I.D. SIZE CODE	FITS TIRE DIMENSIONS
MH 900	24.5" to 30.0" Dia.- 8" to 10.5" Tread -14/15" Rim Dia.
MH 1050	29.0" to 31.5" Dia.- 10.5" to 12.5 Tread - 15/16" Rim Dia.
MH 1450	30.5" to 34.5" Dia.-12" to 17" Tread - 15/16" Rim Dia.

Select, High Grade, Natural Rubber -Lightweight -High Strength;-High Stretch

VINTAGE MIDGET RACING SLICKS

SIZE	P. CODE	T.W.	S.W.	DIA.	CIR.	RIM
450-12	MAM 011	5.4	6.6	21.8	68.5	5
500-12	MAM 012	5.7	7.6	22.8	71.6	6
550-12	MAM 013	6.0	8.2	23.4	73.5	6

Can be grooved for dirt applications. "Authentic" made in the original molds using current race tire technology.

WARRANTY POLICY

Due to the conditions under which they operate, there is NO WARRANTY, GUARANTEE, OR LIABILITY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTIES AS TO MERCHANTABILITY OR FITNESS applicable to M&H RACEMASTER TIRES, and shall not be liable for any consequential or special damages arising out of their use. DRAG RACE TIRES ARE SOLD AS IS! Race tires are not tested, or labeled to meet FMVSS109/ECE36 safety standards and therefore it is illegal to use this product on the street or highway. Any persons selling Drag race tires for such use agrees to indemnify and reimburse M&H Racemaster, Inc. for all loss, damage or liability M&H Racemaster, Inc. may suffer because of such sales.

NEVER attempt to chemically treat or alter the tire and/or tread compound of the tires, such as soaking or use of tread softener. This could result in premature or catastrophic tire failure with resulting serious injury or death.

WARNING

Tire changing should be done by trained personnel using proper tools, procedures and wheels or rims that are manufactured to Tire and Rim Association (T&RA) specifications and tolerances. Failures to follow safe mounting procedures could cause faulty positioning of the tire and cause assembly to burst with explosive force sufficient to cause serious injury or death. Clean rim, lubricate rim and bead with rubber lubricant, install valve core. Always lock wheel on mounting machine or place in safety cage and use extension gauge and hose with clip on air chuck. STAND BACK; NEVER EXCEED 35 PSI TO SEAT BEADS.

ALL M&H RACEMASTER D.O.T. LABELED TIRES have passed D.O.T. requirements. But have reduced tread depth and soft tread compounds designed for racing purposes only on dry pavement, and are not suitable for normal highway use.

General Information

No Warranty

Due to the conditions under which they operate, this manufacturer and Road Racing Services **MAKES NO WARRANTY AND SPECIFICALLY DISCLAIMS ANY WARRANTY (INCLUDING ANY WARRANTY AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE), EITHER EXPRESSED OR IMPLIED**, with respect to this manufacturer's tires, tubes, safety spares or air containers and shall not be liable for any damages whatsoever including, without limitation, consequential or special damages, arising out of their use. The manufacturer's tires are designed and compounded solely for racing purposes and are not tested or labeled to meet FMVSS/ECE Regulations. It is therefore not only dangerous but also illegal to sell for use or use race tires on public streets or highways.

Pressure Recommendations

Consult your tire manufacturer's racing tire dealer for specific recommendations for your local track.

Tire changing should be done by trained personnel using proper tools and procedures. NEVER attempt to install and inflate a tire of one diameter on a rim or wheel of another diameter. All of this tire manufacturer's tires are designed to be used on wheels or rims that are manufactured to Tire and Rim Association (T&RA) specifications and tolerances. Use of this manufacturer's tires on damaged or improper rims can cause the assembly to explode with force sufficient to cause injury or death. When inflating, always lock wheel on mounting machine or place in safety cage and use extension gauge and hose clip on air chuck. **STAND BACK. NEVER EXCEED 35 PSI TO SEAT BEADS.**

Tire Care

The tire manufacturer's tires should not be stored near high temperature, in direct sunlight, around welding areas, in overhead garage areas or around high-voltage electric motors. Long-term storage of the manufacturer's tires is not recommended.

NEVER attempt to patch or repair the manufacturer's tire.

NEVER attempt to chemically or physically treat or alter the manufacturer's tires.

NEVER re-use the manufacturer's tires involved in a vehicle fire under **ANY** circumstances.

Road Racing Services, Inc.
www.racetracktires.com

George M. Ibbotson, Owner/President

2390 W. Dartmouth Ave. Englewood, CO
Mail - P.O. Box 1825 - Englewood, CO 80150-1825

Phone: 303-789-5427
Fax: 303-973-8005
email: george@racetracktires.com